



ALBOND 9000 ALUMINIUM COMPOSITE PANEL 20 YEARS GENERAL WARRANTY

Albond Alüminyum Sanayi ve Ticaret A.Ş.(Albond) warrants that Albond 9000 Aluminium Composite Panels which is covered by this warranty will resist natural indoor and outdoor weathering to the extent that they will confirm to the performance listed below for 20 (twenty) years provided that all conditions of this warranty are first met.

1. Warranty on Aluminium Composite Panel

- a. Albond guarantees that the panel will not delaminate from core material if it is fabricated and installed under normal conditions.
- b. Limited warranty applies only on the side of the product directly exposed to the weather. So topcoat will not peel, flake or crack (except for slight crazing or cracking may occur on break bends after grooving or other fabrication of panels which is accepted in industry as a standart) over no more than 5% of the total surface.
- c. Albond guarentees that, when installed in absence of standing or ponding water, the product will have a uniform and controlled colour and gloss evolution, under the same exposure, without affecting the aesthetics of the project. Non-uniform fading and colour changes are not covered by this limited warranty if they result from the coated surfaces being unequally exposed to sunlight and the elements.
- d. Topcoats will not change color more than 5 CIELAB units. Color measurements are to be made per ASTM D 2244 and only on clean surfaces removing surface deposits and chalk per ASTM D 3964.
- e. Topcoats will not lose gloss higher than 60%. Gloss measurements should be performed according to EN 13523-2.

2. Start Date

The Limited Warranty period shall commence on the date of Albond's initial shipment of product.



3. Maintenance

Cladding and roofing must be inspected and properly maintained once per year in accordance with Albond's "Technical Recommendations" in order for your Limited Warranty to apply. Fully documented and corroborative cleaning records must be kept during the Limited Warranty period and provided to Albond when exercising your Limited Warranty rights.

4. Notification

Albond has to be notified in writing by the customer of a claim within 30 days of the initial identification of any defect indicating a potential failure of the product meeting the specified performance criteria. Notification must include proof of the origin of the product including tracking information on the manufacturing and installation of the product. Time is of then essence, and the failure to make a Limited Warranty claim within this period will eliminate your right to make that claim.

5. Inspection

Albond shall be given opportunity(ies) to inspect the Albond coated roofing or cladding that the customer is claiming to be defective.

6. Corrective Action

In case any product should be found not to be in conformity with the conditions of this Warranty, Albond will bear the full cost of labour and material to replace or refinish the defective portion of the field installation. The decision about the right remedial work will be made at the sole discretion of Albond.

All Warranty work will be performed by Albond or by a company, dealer, contractor, applicator, or distributor selected by Albond. Since there may be a colour variance between the replacement or repainted Product and the originally installed Product due to normal weathering (i.e., exposure to sunlight and extremes of temperature and weather) of the originally installed Product, this condition shall not be indicative of a defect.

The Warranty Period applicable to any refinished, repaired or replaced Product shall be for the then unexpired portion of the Warranty Period applicable to the originally installed Product.



7. Limited Refund

Limited refund period starting after 10 years. During the first 10 year period after the delivery date, the Limited Warranty value will be equivalent to a maximum of 100% of the purchase price of Albond product. From year 11 until year 20 the Limited Warranty value will be the following percentage of the total purchase value:

Years 11-12	80%
Years 13-14	60%
Years 15-16	40%
Years 17-18	20%
Years 19-20	10%

Notwithstanding the refund schedule above, Albond shall determine in its sole discretion what corrective action or remedy will be available under the Limited Warranty.

Albond reserves the right to stop or modify its product lines and coating colours. If the original product is no longer available, Albond may, at its option, either substitute a product or coating of equal value and quality or refund the purchase price of the defective product.

8. Exclusions

This is an anti-weathering limited warranty and does not apply to other causes degradation Albond can not control including panels which,

- has suffered scratches or abrasions during handling or installation;
- has a defect having been caused by the influence or performance of a service or condition, including any residual film, adhesives, sealants or mastics.
- having been continuously exposed to the temperature as of 80 °C or above.
- is stored or installed in a way that have a less than 5° degree pitch and areas subject to ponding of water or that otherwise are subject to retention of water or other contaminants, including direct or indirect contact to corrosive materials.
- is not having been annually inspected and properly maintained. Fully documented and corroborative cleaning records must be kept for the period of the Warranty.



- f. has been exposed to improper maintenance or chemical cleaning agents.
- g. is installed in aggressive atmosphere such as those with chemical fumes, chemical deposits, sand, dirt or grease.
- h. have been re- or post painted; touched up.
- i. have been installed within 1 km (measured from mean high tide) of any body of salt water and/or sea.
- j. is perforated.
- k. has any damage due to fabrication and/or installation of the panels.
- l. has any damage or failure caused by external forces, explosions, fire, lightning, earthquake, abnormal winds, riots, civil commotion, war, radiation, flood or other similar or dissimilar occurrences beyond Albond's control.

9. Notes

1. The protective film should be removed from the coated surface of Albond aluminium composite panel within 2 months after completion of installation.
2. Panels must be installed in one direction on facade to avoid the shade difference.

TEKİRDAĞ, 2020,
Albond Alüminyum San. ve Tic. A.Ş